



CPVC Schedule 80 Tank Adaptor, Viton

Standards

- Manufactured to ASTM F439: Standard Specification for Chlorinated Polyvinyl Chloride (CPVC) plastic pipe fittings, Schedule 80
- Approved by NSF International for use with potable water (NSF Std 61: Drinking Water System Components - Health Effects)



Dimensions



DN	NB	L mm	L1 mm	M mm	M1 mm	N mm	R mm	Weight kg	Part No
7.5mm	¼"	63.50	46.03	38.09	26.98	30.16	12.70	0.049	8170V-002C
10mm	⅜"	63.50	46.83	41.27	24.60	22.22	12.70	0.054	8170V-003C
15mm	½"	74.61	55.56	50.80	30.16	28.57	15.87	0.104	8170V-005C
20mm	¾"	74.61	55.56	57.15	41.27	23.81	15.87	0.122	8170V-007C
25mm	1"	84.13	65.08	66.67	50.80	26.98	15.87	0.199	8170V-010C
32mm	1 ¼"	87.31	66.67	79.37	58.73	23.81	15.87	0.204	8170V-012C
40mm	1 ½"	92.07	71.43	92.07	68.26	20.63	15.87	0.471	8170V-015C
50mm	2"	104.77	82.55	123.82	82.55	26.98	19.04	0.603	8170V-020C
65mm	2 ½"	123.03	98.42	133.35	96.83	32.54	25.40	1.179	8170V-025C
80mm	3"	139.70	114.30	152.39	115.88	42.86	25.40	1.220	8170V-030C
100mm	4"	127.00	101.60	190.50	139.70	11.11	31.75	1.542	8170V-040C
155mm	6"								8170V-060C
195mm	8"	219.07	177.79	328.61	260.34	12.70	38.10	7.847	8170V-080C